Direct-View LED Traffic Controller TCL734GGR-110

PRODUCT NUMBER

CABINET DIMENSIONS

7" H x 34" W x 2.5" D



ILLUMINATION SOURCE
Super bright, wide viewing angle LEDs
Available in green, red, blue, amber, and white LEDs
Messages "blankout" when turned off, eliminating confusion
Long life, solid state lighting

ELECTRICAL

Integrated solid state power supply
Standard Voltage: 120 VAC, Optional Voltages: 9-36 V, 240 VAC, 277 VAC
Maximum amps per lighted message (at 120 V) shown in the table below
UL/CUL approved for wet locations

CONSTRUCTION

Faces: Single Faced Sign Extrusions (TCL): Slim line continuous, corrosion resistant, aluminum housing 2.5" deep

Face Material: Impact Resistant, smoked tinted Polycarbonate 1/8" thick.

FINISH

Standard Cabinet Color: Duranodic Bronze Custom colors available upon request

MESSAGE	COLOR	HEIGHT	AMPS
	Green Wide Angle Oval		0.02
OPEN	Green Wide Angle Oval	3.5"	0.03
CLOSED	Red Wide Angle Oval	3.5"	0.03

Product View

NOTE: Sign image may not exactly represent the finished product. For illustration purposes only.



